



Vision OmniPrint

Textured, Non-Slip Vinyl with Repositionable Adhesive

Vision OmniPrint is the ultimate, one-step solution for indoor floors & walls, as well as sidewalk graphics! Designed for short to medium term, indoor & outdoor applications. Vision OmniPrint works great on carpet, tile, concrete, wood, stone, metal, glass and painted surfaces. Perfect for tradeshow, retail POP, wall murals, kids rooms, etc...

Repositionable, Dimensionally Stable & Durable

	Front or Back-lit	Indoor/Outdoor	Banner	Building Wrap	Trade Shows	Display Systems	Doors, Walls & Floors	Retail/POP	Sidewalk Graphics
APPLICATIONS		●			●		●	●	●

ADVANTAGES

- Textured, Non-Slip Vinyl with Dimensionally Stable Fabric Backing & Repositionable Adhesive
- No Lamination Required!
- Slip Resistant (ASTM D-2047, ASTM C 1028-07 & R12 Certified)
- Sticks to Almost Any Surface
 - Tile Carpet Metal Painted Surfaces
 - Glass Wood Stone Etc..
- Easy to Install and Remove, Panels Pull Up in One Piece.
- Repositionable & No Adhesive Residue
- Universal Printability: Solvent, Eco-Solvent, Latex & UV Digital Prints and Screen Printing

GENERAL ADVICE

- Rounding Corners helps Prevent Edge Lift
- For Critical Substrates and Surfaces, Please Test in an Inconspicuous Location Prior to Final Application.

www.visiondoesit.com

info@visiondoesit.com



Vision OmniPrint

Textured, Non-Slip Vinyl with Repositionable Adhesive

MATERIAL - Vision OmniPrint

- Textured Vinyl Surface with Fabric Backing
- Printable Bright White Front Side
- Repositionable Solvent Acrylic Adhesive
- 8mil Thickness (200 microns)
- Available in 48"x82' & 48"x164' Rolls
- B1 & M1 Fire Certificates
- ASTM E-84, ASTM E-648 & ASTM E-662

LINER

- Polyethylene Coated Paper

PRINTING METHODS

- Digital - Solvent, Eco-Solvent, Latex & UV
- Screen Printing

HUMIDITY & SOLVENT RESISTANCE

- Good - Resistant to Mild Acids, Alkalis and Salt Solutions

REMOVAL TEMPERATURES

- +50°F to +86°F (+10°C to +30°C)

APPLICATION & SERVICE RANGE TEMPS

- +0°F to +122°F (-17°C to +50°C)

SHELF LIFE

- 12 Months Stored at +68°F(+20°C)
and a 50% Relative Humidity

DURABILITY

- Indoor Floor Applications: 1-3 Months
(Depending on Traffic)
- Indoor Wall Applications: 24-36 Months
- Outdoor Sidewalk Applications: 1-3 Months
- Clean Removal with No Adhesive Residue

APPLICATION

- Surface Must Be Clean, Dry & Above 0°F(-17°F)
- Apply with A Hard Rubber Roller to Ensure Adequate Adhesion

IMPORTANT INFORMATION

Vision Graphics products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated on this Technical Specification sheet.

Vision Graphics will replace or refund the price of any Vision Graphics materials found not to meet our product specifications. In no case shall Vision Graphics be liable for any direct, indirect, or consequential damages, including labor or non-Vision Graphics material charges.

**The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Note: For critical substrates and surfaces, please test in an inconspicuous location prior to final application.