

Vision Outdoor Blockout – 18oz

Vision Outdoor Blockout 18 oz. is a heavy duty blockout banner material for indoor or outdoor applications. The uniquely woven 1000 x 1000 scrim provides strength and stability under harsh weather conditions. Vision Pole Banner 18 oz. is designed for two-sided applications where complete opacity is required. Both sides of the material have a matte finish and are compatible for use with solvent, eco-solvent, UV and screen printing. Available in widths from 38" to 196".



	Front or Back-lit	Indoor/ Outdoor	Banner	Billboard	Block-out	Building Wrap	Trade Shows	Display Systems	Truckside	Retail/ POP	Movie Banner
Vision Outdoor Blockout – 18oz	FR	IN OUT	•	•	•			•	•		

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH		
Support Cloth	DIN60001	Polyester	Polyester		
Yam dtex	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier		
Type of Coating	N/A	PVC	PVC		
Total Weight	DIN EN ISO 2286-2	610 g/m²	18 oz/yd²		
Tensile Strength	DIN 53354	2420 x 2058 N/5cm	276 x 235 lbs/in		
Tear Strength (warp/weft)	DIN 53363	294 x 245 N	34 x 28 lbs		
Flame Resistance	DIN 4102	NFPA-701, B1, Title 19, CSFM			
Low Temperature (No Crack at:)	DIN53357 BS3425	-30°C	-22°F		
RF Weldable (Heat Sealable)	DIN 53354	Yes	Yes		
Fungus Resistance	ASTM G21	Yes			


All statements, technical information and recommendations about Vision Graphics substrates are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Vision Graphics products are sold with the understanding that the purchaser has independently assumed responsibility in determining the suitability of such product for its purposes. +1/-2 variance is allowed on all specs.

It is the responsibility of purchasers to independently verify, prior to use, the suitability of the products for their specific applications and print methods. SBR/Vision Graphics cannot be held liable for any misuse, damage or losses as specified in its product warranty. Subject to change without notice.






Finishing Type 05 (and the previous type 04). Standard banner pocketing. Can be welded or sewn. The outside edge of the pocket can be aligned to the Live Area or Additional Material can be included. Options include single or double pockets and/or reinforcement.



Finishing type 06. Standard billboard finishing. Can be welded or sewn. Options include single or double pockets and/or reinforcement. This type is most economical but limits the amount of bleed.



Bleed:

Additional Material:

Any additional material added between the Live Area and the Finished Edge.

Safety Margin:

too close to the edge.

Image that is printed beyond the Live Area to cover the edges of the structure or "just in case" the structure measurements are slightly off or the image is not installed perfectly. An arbitrary distance from the Live Area inward to prevent critical copy/artwork from being

Frontlit Bulletin Nomenclature & Measuring Guide

The terms and measurements required to accurately produce a Frontlit sign can be confusing. Communicating with everyone from artist to installer is simplified when everyone is speaking the same language.

