



## 3M™ Scotchcal™ Graphic Film

IJ35-10 & IJ35-20

### Product Features

- Excellent imageability, permanent adhesive, attractive price.
- Available in gloss and matte finishes
- Pressure sensitive adhesive
- Permanent
- Expected Performance Life of 5 years (unwarranted period for unprinted film with no graphic protection, applied to a flat, vertical, outdoor surface)
- Recommended uses include: Short to long-term, indoor and outdoor promotional graphics, signs, trade show and point-of-purchase displays, exhibits and architectural applications

	Front or Back-lit	Indoor/Outdoor	Vehicles Straight Trucks Semi-trailers Bus	Decals, Emblems & Striping	Indoor & Outdoor Graphics & Signs	POP	Identification graphics & Warning Labels	Advertising & Marketing
3M™ Scotchcal™ Graphic Film	FR	BOTH		●	●	●	●	●

CHARACTERISTIC	VALUE	
	IJ35-10	IJ35-20
<b>Finish</b>	Gloss	Matte
<b>Material</b>	Cast Vinyl	
<b>Film Color</b>	White, opaque	
<b>Thickness</b>	Without adhesive: 3.25 mil (0.081 mm) With adhesive: 4 mil (0.102 mm)	
<b>Adhesive</b>	Pressure sensitive	
<b>Finished Graphic Application Recommendation</b>	<b>Surface type:</b> Smooth, flat and simple curved surfaces <b>Substrate type:</b> Metal, rigid plastic and painted surfaces <b>Application temperature:</b> 40 °F to 100 °F (4 °C to 38 °C) <b>Application method:</b> Dry	
<b>Temperature Range After Application</b>	-59 °F to 192 °F (-50 °C to +90 °C) (Not for extended periods of time at the extremes)	
<b>Maintenance and Cleaning</b>	Use a cleaner designed for high-quality painted surfaces. The cleaner must be wet, non-abrasive, without solvents, and have a pH value between 3 and 11 (neither strongly acidic nor strongly alkaline).	

WALL COVERINGS

All statements, technical information and recommendations about Vision Graphics substrates are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Vision Graphics products are sold with the understanding that the purchaser has independently assumed responsibility in determining the suitability of such product for its purposes. +1/-2 variance is allowed on all specs.

It is the responsibility of purchasers to independently verify, prior to use, the suitability of the products for their specific applications and print methods. SBR/Vision Graphics cannot be held liable for any misuse, damage or losses as specified in its product warranty. Subject to change without notice.